




Front View



Optional item - Front door

Features

- High-density design for space saving
- Hot swap design for maintenance and management
- Supports 8 x 12Gb/s 3.5" hot swap drive bays
- Supports 4 x 12Gb/s 2.5" OS drive or 2 x 12Gb/s 2.5" OS drive with 1 x slim CD-Rom option
- Tool-less drive trays for 3.5" & 2.5" HDD
- Supports single and redundant power supplies
- 7 x low profile slots
- Front access USB 3.0 port

Rear View




Specifications

Dimensions (W x D x H)	mm : 430 x 680 x 88		
	inches : 17 x 26.8 x 3.5		
Industry Standard	EIA-RS310D		
Material	Heavy-duty preplated SPGC cold-rolled steel		
Color	Front Panel : Black		
Cooling	3 x 80x25mm PWM easy swap fans		
Power Supply	800W 1+1 redundant power supply PMBus 1.2 80+ Platinum		
	Options	<ul style="list-style-type: none"> • 2U 550W single • 2U 550W 1+1 redundant PSU 	
Expansion Slots	7 low profile		
Front Panel	System power on/off, system reset and 1 x USB 3.0 port		
LED Indicators	Power, LAN, Drive and Alert		
System Board	12"(W) x 13"(D) E-ATX MB		
Drive Bays	External	3.5" hot swap	8
		2.5" hot swap	Option: 2 x 2.5" (7mm)
	Internal	2.5"	Options: • 4 x 2.5" internal • 2 x 2.5" internal and 1 x slim DVD-Rom
	Peripheral Drive	Slim DVD-ROM	


Backplane	2 x 4-port 12Gb SATA/SAS backplanes with SFF-8643 connector	
Storage Temperature	0°C(32°F) ~ 50°C(122°F)	
Humidity	5%~95% non-condensing	
Gross Weight	(w/ PSU & Rail)	kgs : 20.5
		lbs : 45
Packaging Dimensions	(W x D x H)	mm : 645 x 835 x 234
		inches : 25.4 x 32.9 x 9.2
Cubic Feet	3.98	
Container Load Quantity	20'	180
	40'	360
	40' H	400
Mounting	Standard	28" tool-less slide rail



Top View



(Power supply is optional. Motherboard is not included.)



Ordering Information

SKU Number	Description
XE1-2KT00-03	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 550W CRPS redundant power supply, 2x top plate HDD + CD-ROM plate, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-04	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 550W CRPS redundant power supply, 2x top plate HDD + 2x 2.5" OS plate, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-06	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 550W CRPS redundant power supply, 2x top plate HDD + 2x 2.5" OS plate, 2x 7mm 2.5" hot-swap OS, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-07	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 800W CRPS redundant power supply, 2x top plate HDD + CD-ROM plate, 2x 7mm 2.5" hot-swap OS, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-08	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 550W CRPS redundant power supply, 2x top plate HDD only, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-09	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 650W single power supply, 2x top plate HDD only, rail, 2x 4-port 12Gb SATA/SAS backplane
XE1-2KT00-10	2U 8x 3.5" hot-swap bays, tool-less 3.5" and 2.5" HDD tray, 800W CRPS redundant power supply, 2x top plate HDD + 2x 2.5" OS plate, 2x 7mm 2.5" hot-swap OS, rail, 2x 4-port 12Gb SATA/SAS backplane

RSC-2KT