

1U4LW-B650/2L2T



- 1U Rackmount with 1, 80-PLUS Gold, 400W PSU
- Single Socket AM5 (LGA 1718), supports AMD EPYC™ 4005/4004 and AMD Ryzen™ 9000/8000/7000 Series Processors
- 4 DIMM slots (2DPC), supports DDR5 ECC/non-ECC UDIMM
- 4 hot-swap 3.5" SATA drive bays
- 1 FH PCIe4.0 x16
- Supports 1 M.2 (PCIe5.0 x4)
- 2 RJ45 (10GbE) by Broadcom BCM57416
- 2 RJ45 (1GbE) by Intel® i210
- 1 HDMI, 1 DisplayPort
- Remote Management (IPMI)

**HDMI™ (High-Definition Multimedia Interface)**

This motherboard supports HDMI™ (High-Definition Multimedia Interface) which is an interface standard for transferring uncompressed video data and delivering multi-channel audio through a single cable. Both video and audio data signals transferred through the HDMI™ interface are digital without being converted into analog, therefore it delivers the richest pictures and the most realistic sounds.

SPECIFICATIONS

System	
Form Factor	1U Rackmount
Dimensions	534.35 x 430 x 43.3 mm (21" x 16.9" x 1.7")
Support MB	B650D4U-2L2T/BCM
Front Panel	
Buttons	Power w/ LED, UID w/LED, System reset
LEDs	LANs, HDD activity, System health
I/O Ports	2 Type-A (USB3.2 Gen1)
External Drive Bay / Storage	
Front Side Drive Bay	4 Hot-swap 3.5" SATA drive bays
Internal Side	1 M-key (PCIe5.0 x4), supports 2280/2242 form factor [CPU]
Power Supply	
Type	Single PSU
Output Watts	400W
Efficiency	80-PLUS Gold
System Fan	
Fan	5 PWM Hot-swap 40x28 mm fans
Processor System	
CPU	Supports AMD EPYC™ 4005/4004 and AMD Ryzen™ 9000/8000/7000 Series Processors
Socket	Single Socket AM5 (LGA 1718)
Thermal Design Power	Up to 170W *Based on Cinebench R23 tool to meet AMD criteria
Chipset	AMD B650
System Memory	
Supported DIMM Quantity	4 DIMM slots (2DPC)
Supported Type	DDR5 288-pin ECC/non-ECC UDIMM
Max. Capacity per DIMM	48GB
Max. DIMM Frequency	5600 MHz (1DPC); 3600 MHz (2DPC)
Voltage	1.1V
PCIe Expansion Slots (SLOT7 close to CPU)	
PCIe x 16	Rear: 1 FH PCIe4.0 x16 via RB1UX16_G4
Ethernet	
Additional GbE Controller	Broadcom BCM57416: 2 RJ45 (10GbE) Intel® i210: 2 RJ45 (1GbE)
Server Management	
BMC Controller	ASPEED AST2600

IPMI Dedicated GLAN	1 Realtek RTL8211F for dedicated management GLAN
Graphics	
Controller	ASPEED AST2600: 1 DB15 (VGA), 1 (15-pin) header AMD Processors with Graphics: 1 HDMI, 1 DisplayPort
Rear I/O	
UID Button/LED	1 UID button w/ LED
Video Port	1 DB15 (VGA), 1 DisplayPort, 1 HDMI
Serial Port	1 DB9 (COM)
USB 3.2 Gen1 Port	4 Type-A (USB3.2 Gen1)
RJ45	2 RJ45 (10GbE) 2 RJ45 (1GbE) 1 dedicated IPMI
System BIOS	
BIOS Type	AMI UEFI BIOS; 256Mb (32MB) SPI Flash ROM
BIOS Features	Plug and Play, ACPI 6.4 compliance wake up events, SMBIOS 3.5
Hardware Monitor	
Temperature	CPU, DDR, MB, Card Side, Chipset, 10G LAN, M.2 slot
Fan	Fan Tachometer, Multi-Speed Control, CPU Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature)
Voltage	VOLT_3VSB, VOLT_5VSB, VOLT_P0_VCORE, VOLT_P0_VSOC, VOLT_VMEM, VOLT_VMISC, VOLT_1.8V_PT21, VOLT_VSUS10, VOLT_VDD10, VOLT_V10_PHY_DIG, VOLT_VDD_1P8, VOLT_MD_VDDO, VOLT_BAT, VOLT_3V, VOLT_5V, VOLT_12V
Supported OS	
OS	Microsoft® Windows: - Windows® 10 (64 bit) - Windows® 11 (64 bit) Linux: - RedHat Enterprise Linux Server 8.7 (64bit) - CentOS 8.5 (64 bit) - SUSE SLES 15.4(64 bit) / 15.2(64 bit) - Ubuntu 22.04.1 (64 bit) / 21.10 (64 bit) / 21.04 (64 bit) Hypervisor: - VMware® ESXi 8.0 / 7.0 U3g
Environment	
Temperature	Operation temperature: 10°C ~ 35°C / Non operation temperature: -40°C ~ 70°C
Humidity	Non operation humidity: 20% ~ 90% (Non condensing)

The specification is subject to change without notice in advance. ASRock Rack is the official trademark for ASRock Rack Inc., all the covers need to remain the original brand name without any modification. All other brands, names and trademarks are the property of their respective owners.



COMPANY NEWS & EVENTS

[About Us](#)

[Contact Us](#)

[Where to Buy](#)

[Press Releases](#)

[Media Reviews](#)

[Events](#)

SUPPORT

[Technical](#)

[Support](#)

[Technical](#)

[FAQs](#)

[QVL](#)

E-NEWS SUBSCRIPTION

Email address...

