



## E3C256D2I

- mini-ITX (6.7" x 6.7")
- Supports Intel® Xeon® E-2300 and 10th Gen Intel® Pentium® series processors
- 2 DIMM slots (1DPC), supports DDR4 ECC/non-ECC UDIMM
- 1 PCIe4.0 x16
- 2 OCuLink (PCIe3.0 x4 or 4 SATA 6Gb/s)
- Supports 1 M.2 (PCIe4.0 x4)
- 8 SATA 6Gb/s
- 2 RJ45 (1GbE) by Intel® i210
- Supports ATX PSU or 12V DC-in
- Remote Management (IPMI)

## Specifications

Physical Status	
Form Factor	mini-ITX
Dimensions	6.7" x 6.7" (170.2mm x 170.2mm)
Processor System	
CPU	Supports Intel® Xeon® E-2300 and 10th Gen Intel® Pentium® series processors
Socket	Single Socket H5 (LGA1200)
Chipset	Intel® C256
System Memory	
Supported DIMM Quantity	2 DIMM slots (1DPC)
Supported Type	Supports DDR4 288-pin ECC/non-ECC UDIMM
Max. Capacity per DIMM	ECC/non-ECC UDIMM: up to 32GB
Max. DIMM Frequency	ECC/non-ECC UDIMM: max. 3200*MHz *Up to DDR4 2666MHz when installing 10th Gen Intel® Pentium® Series Processors
Voltage	1.2V
PCIe Expansion Slots (SLOT7 close to CPU)	
PCIe x 16	SLOT7: PCIe4.0* x16 [CPU] *SLOT7 supports PCIe3.0 only when installing 10th Gen Intel® Pentium® Series Processors
Other PCIe Expansion Connectors	
M.2 slot	1 M-key* (PCIe4.0 x4); support 2280 form factor [CPU] *M.2 will not function when installing 10th Gen Intel® Pentium® Series Processors
OCuLink	2 OCuLink (PCIe3.0 x4 or 4 SATA 6Gb/s) [PCH]
SATA/SAS Storage	
PCH Built-in Storage	Intel® C256 (8 SATA 6Gb/s; RAID 0/1/5/10): 2 OCuLink
Ethernet	
Additional GbE Controller	Intel® i210: 2 RJ45 (1GbE)
Server Management	
BMC Controller	ASPEED AST2500
IPMI Dedicated GLAN	1 x Realtek RTL8211E for dedicated management GLAN
Graphics	
Controller	ASPEED AST2500
VRAM	DDR4 256MB

Rear I/O	
UID Button/LED	1 button w/ LED
VGA Port	1 DB15
USB 3.2 Gen1 Port	2 Type-A (USB3.2 Gen1)
USB 3.2 Gen2 Port	2 Type-A (USB3.2 Gen2)
RJ45	2 RJ45 (1GbE)
Internal Connector/Headers	
Power Connector	1 (4-pin, ATX PSU signal) w/ ATX 24-pin adapter cable, 1 (8-pin, ATX 12V) support 12V DC-in
Other Power Connectors	1 ATX (4-pin) for HDD power when using 12V DC-in power source
Auxiliary Panel Header	1 (9-pin): chassis intrusion, system fault LED, LAN activity LED
System Panel	1 (9-pin): power switch, reset switch, system power LED, HDD activity LED
VGA header	1
Fan Header	3 (4-pin)
Thermal Sensor Header	1
TPM Header	1 (13-pin, SPI)
SGPIO Header	1
SMBus header	1
PMBus header	1
IPMB Header	1
Clear CMOS	1 (contact pads)
USB 3.2 (Gen1) Header	1 (19-pin, 2 USB3.2 Gen1)
LED Indicators	
Standby PWR LED 5vsb	1
Fan Fail LED	3
BMC heartbeat LED	1
System BIOS	
BIOS Type	AMI UEFI BIOS; 256 Mb (32MB) SPI Flash ROM
BIOS Features	Plug and Play, ACPI 6.2 compliance wake up events, SMBIOS 3.3, ASRock Rack instant flash
Hardware Monitor	
Temperature	CPU, MB, Card side, TR1
Fan	Fan Tachomete, CPU Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature), Multi-Speed Control
Voltage	+12V, +5V, +3.3V, CPU Vcore, DRAM,V1.05M,+BAT, 3VSB, 5VSB
Supported OS	
OS	<p>Microsoft® Windows® :</p> <p>Server 2019 (64 bit)</p> <p>Server 2022 (64 bit)</p> <p>Linux :</p> <p>RedHat Enterprise Linux Server 8.6 (64 bit) / 8.3 (64 bit)</p> <p>CentOS 8.5 (64 bit) / 8.3 (64 bit)</p> <p>SUSE Enterprise Linux Server 15 SP2 (64 bit)</p> <p>Ubuntu Ubuntu 21.04 (64 bit) / Ubuntu 20.10 (64 bit)</p> <p>Hypervisor :</p> <p>VMWare® ESXi 7.0U3d / vSphere 7.0U3d</p> <p>* Supports UEFI BOOT only</p>
Environment	
Temperature	Operation temperature: 10°C ~ 35°C / Non operation temperature: -40°C ~ 70°C
Humidity	Non operation humidity: 20% ~ 90% ( Non condensing)

The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.