



## GENOAD8UD-2T/X550

- 10.4" x 10.5"
- Single Socket SP5 (LGA 6096), supports AMD EPYC™ 9004 (with AMD 3D V-Cache™ Technology) and 97x4 series processors
- 8 DIMM slots (1DPC), supports DDR5 RDIMM, RDIMM-3DS
- 4 PCIe5.0 / CXL1.1 x16
- 2 MCIO (PCIe5.0 x8 or 8 SATA 6Gb/s), 2 MCIO (PCIe5.0 x8), 1 MCIO (PCIe5.0 x4)
- Supports 2 M.2 (PCIe5.0 x4)
- Up to 16 SATA 6Gb/s
- 2 RJ45 (10GbE) by Intel® X550-AT2
- Remote Management (IPMI)
- Support ATX PSU or 12V DC-IN

### Specifications

Dimensions	10.4" x 10.5"
<b>Processor System</b>	
CPU	Supports AMD EPYC™ 9004 (with AMD 3D V-Cache™ Technology) and 97x4 series processors
Socket	Single Socket SP5 (LGA 6096)
Chipset	System on Chip
<b>System Memory</b>	
Supported DIMM Quantity	8 DIMM slots (1DPC)
Supported Type	Supports DDR5 288-pin RDIMM, RDIMM-3DS
Max. Capacity per DIMM	RDIMM: 64GB (2R) RDIMM-3DS: 512GB (2S8Rx4)
Max. DIMM Frequency	4800 MHz
Voltage	1.1V
<b>PCIe Expansion Slots (SLOT7 close to CPU)</b>	
PCIe x 16	SLOT6: PCIe5.0 / CXL1.1 x16 □ SLOT5: PCIe5.0 / CXL1.1 x16 SLOT4: PCIe5.0 / CXL1.1 x16 SLOT3: PCIe5.0 / CXL1.1 x16
<b>Other PCIe Expansion Connectors</b>	
M.2 slot	2 M-key (PCIe5.0 x4); support 2280/2260/2242/2230 form factor
Others	2 MCIO (PCIe5.0 x8) 2 MCIO (PCIe5.0 x8 or 8 SATA 6Gb/s) 1 MCIO (PCIe5.0 x4)
<b>SATA/SAS Storage</b>	
PCH Built-in Storage	AMD EPYC™ 9004 (16 SATA 6Gb/s); 2 MCIO
<b>Ethernet</b>	
Additional GbE Controller	Intel® X550-AT2: 2 RJ45 (10GbE)
<b>Server Management</b>	
BMC Controller	ASPEED AST2600
IPMI Dedicated GLAN	1 Realtek RTL8211F for dedicated management GLAN
<b>Graphics</b>	
Controller	ASPEED AST2600
VRAM	DDR4 512MB
<b>Rear I/O</b>	

UID Button/LED	1 UID button w/ LED
VGA Port	1 DB15 (VGA)
USB 3.2 Gen1 Port	2 Type-A (USB3.2 Gen1)
RJ45	2 RJ45 (10GbE) 1 dedicated IPMI
<b>Internal Connector/Headers</b>	
Power Connector	1 (4-pin, ATX PSU signal) w/ ATX 24-pin adapter cable, 3 (8-pin, ATX 12V) support 12V DC-in
Other Power Connectors	1 (6-pin) for HDD power
Auxiliary Panel Header	1 (18-pin): chassis intrusion, system fault LED, LAN1/LAN2 activity LED, locate, SMBus
System Panel	1 (9-pin): power switch, reset switch, system power LED, HDD activity LED
COM Header	1
Speaker Header	1 (4-pin)
Fan Header	6 (6-pin)
Thermal Sensor Header	1
TPM Header	1 (13-pin, SPI)
SGPIO Header	2
HSBP	1
SMBus header	1
PMBus header	1
IPMB Header	1
Clear CMOS	1 (contact pads)
USB 3.2 (Gen1) Header	1 (19-pin, 2 USB3.2 Gen1)
NMI Header	1
<b>LED Indicators</b>	
Standby PWR LED 5vsb	1 (5VSB)
Fan Fail LED	6
BMC heartbeat LED	1
<b>System BIOS</b>	
BIOS Type	AMI UEFI BIOS; 256 Mb (32MB) SPI Flash ROM
BIOS Features	ASRock Rack Instant Flash, ACPI 6.4 and above compliance wake up events, SMBIOS 3.5.0 and above, Plug and Play(PnP)
<b>Hardware Monitor</b>	
Temperature	CPU, MB, TR1 Temperature sensing
Fan	CPU/Rear/Front Fan Tachometer CPU Quiet Fan (Allow Chassis Fan Speed Auto-Adjust by CPU Temperature) CPU/Rear/Front Fan Multi-Speed Control
Voltage	VCORE,VCCSA,VCCM,3V, 5V, 12V, +BAT, 3VSB, 5VSB,VCCIO,+2.5V_VPP
<b>Supported OS</b>	
OS	Microsoft® Windows: - Server 2019 (64bit) - Server 2022 (64 bit)  Linux: - RedHat Enterprise Linux Server 8.6 (64bit) / Server 8.7 (64bit) / Server 9.0 (64bit) / Server 9.1 (64bit) - SUSE SLES 15.4(64 bit) - Ubuntu 20.04.5 (64 bit) / 22.04 (64 bit) / 22.10 (64 bit)  Hypervisor:: - VMWare® ESXi/ 7.0 U3i / 8.0 - CITRIX Hypervisor 8.2.1
<b>Environment</b>	
Temperature	Operation temperature: 10°C ~ 35°C / Non operation temperature: -40°C ~ 70°C
Humidity	Non operation humidity: 20% ~ 90% ( Non condensing)

The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.