

Application:

- Recommend for Intel® Xeon® Platinum / Gold Family Processor (products formerly Skylake), Socket FCLGA3647
- For Narrow ILM Only
- Active Cooler for 1U Server

Overall Specification:

- Dimension: 108 x 81 x 28 mm
- Weight: 500g
- Material: Copper1100 Heatsink with Vapor Chamber Base
- 8013 Aluminum PWM Blower for Heat Exhausting
- Convenient Heat Sink Screw captive mounting
- Thermal Grease Shin-Etsu 7762 Pre-printed
- Support CPU power up to 205 Watts heat dissipation
- Includes both Fabric and Non-Fabric Package Carriers

Blower Specification:

- Model Number: DB128013BU-PWMG
- Dimension: Ø80 x 13 mm
- Bearing: Ball Type, Double
- Rated Voltage: 12V
- Rated Speed:
 - At Duty Cycle 0~20%: 1500 ± 200 RPM
 - At Duty Cycle 50%: 4000 ± 10% RPM
 - At Duty Cycle 100%: 8000 ± 10% RPM
- Rated Input Power:
 - o At Duty Cycle 0~20%: 1.44 W
 - o At Duty Cycle 50%: 4.80 W
 - o At Duty Cycle 100%: 19.2 W
- Rated Airflow:
 - At Duty Cycle 0~20%: 4.30 CFM
 - At Duty Cycle 50%: 11.6 CFM
 - At Duty Cycle 100%: 22.80 CFM



Rated Static Pressure:

At Duty Cycle 0~20%: 3.0 mm-H₂O
At Duty Cycle 50%: 21.0 mm-H₂O
At Duty Cycle 100%: 83.8 mm-H₂O


Rated Acoustical Noise:

At Duty Cycle 0~20%: 25.6 dBA
At Duty Cycle 50%: 46.9 dBA
At Duty Cycle 100%: 62.0 dBA


Lead Wire Pin Out:

- o Pin#1-Black(-)
- o Pin#2- Yellow(+)
- Pin#3- Green(Tachometer/ Signal Output)
- o Pin#4- Blue (PWM)

Lead Wire Pin Out Diagram :



Active Cooler B16 Thermal Performance Curve:



Fan Speed (RPM)

