

# ToughArmor

# MB601VK-1B

# ICY DOCK®

## U.2 NVMe SSD Hot-Swap Mobile Rack for 3.5" Bay

www.icydock.com



### Maximum Heat Dissipation

All-around ventilated airflow holes



### Hot-Swappable U.2 Design

up to 10,000+ insertion / removal



**Additional Drive Protection**  
2 Segment Keylock

### Supports Full NVMe Bandwidth

Transfer speed up to 32Gb/s



**SATA III**  
6 Gbps



**NVMe**  
32 Gbps



### Full Metal Construction

Protect against bumps & drops



## ToughArmor MB601M2K-1B Features & Specs

- Fits 1x 2.5" U.2 NVMe SSD, up to 15mm in height
- Installs into any standard external 3.5" device bay or floppy bay
- Uses a U.2 port (SFF-8639) to connect, requires NVMe host
- Supports the full NVMe bandwidth specification of 32 Gbps
- Ruggedized full-metal enclosure meeting flammability requirements
- 2-segment key lock for additional physical security
- Eagle-hook tray latch securely holds the tray inside the enclosure
- EMI Grounding – protects hard drives from electrical damage
- Anti-Vibration Technology (AVT) reduces noise and protects against environmental damage
- Active Power Technology (APT) saves power by shutting the device down when no drive is installed.
- Industry leading 3-year warranty against all defects
- Complimentary support from professionally trained US-based technical support agents

Model Number	MB601VK-1B
Color	Black
Compatible Drive Type	1 x 2.5" U.2 NVMe SSD (up to 15mm height)
Number of Drives	1
Device Interface	1 x U.2 connector (SFF-8639)
Power Input	Via U.2 (SFF-8639)
Device Fit	1 x External 3.5" Drive Bay
Transfer Rate	Up to 32Gbps
Support Hot-Swap	Yes
Drive Cooling	Metal heat dispersion with passive cooling
Material	Metal with ABS Plastic
Dimension (W x H x D)	168.7 x 101.2 x 25.4
Product Net Weight	Device, Manual, Screws, Keys
Package Contents	441g