Inter-Tech Elektronik Handels GmbH

IPC 4U-4724



IPC 4U-4724

The **IPC 4U-4724** is the perfect rack for a small and cost-effective storage system. Due to the excellent material quality, in combination with excellent workmanship, Inter-Tech has created the basis for an extremely variable case.

The case offers the possibility of installing a maximum of 24x 2.5" or 3.5" hot-swap hard disks, as well as two 2.5" internal hard disks. The IPC 4U-4724 is equipped with five fans installed as standard, of which there are three 120mm internally directly behind the drive brackets. Two additional 80mm fans on the back reliably ensure optimal cooling.

Additional extras such as the reusable and perforated slot brackets, USB 2.0 connections and the case lid with snap-in closures complete this excellent overall package.



IPC 4U-4724

Specifications

Motherboard Mini ITX, μΑΤΧ, ΑΤΧ, eATX, SSI EEB maximal motherboard size BxT: 305mm x 345mm, 12" x 13.5" Drive bays 24x 2.5" or 3.5" Hot-Swap (max. 6G) 2x mounting bracket for each 1x 2.5" Front connectors USB 2.0: 2 Cooling system Internal: 3x 120mm (3x serial, 4pin at backplane) Rear: 2x 80mm (2x serial, molex connector) Controls Power button Reset button UID button **LED** Power **HDD** activity 2x network activity Alert Temperature alert Power supply ATX PSU Redundant PSU Material 1.0-1.2mm Steel Maximum CPU cooler height 155mm Maximum graphics card length 340mm Shipping unit: 1 piece Packing units Pallet: 14 pieces 24 months Warranty Article number 88887354 4260455647250 EAN-Code Scope of delivery Screws Mounting bracket for ATX (pre-mounted) and 4U redundant power supplies **Features** Standard 3x 120mm and 2x 80mm fans

7x perforated slot brackets

Lid with snap-in lock

2x 12-way S-ATA/SAS hot-swap backplane with 3x SFF-8087 socket1

The backplane is only suitable for operation on a SAS controller with a SFF-8087 connector.

Adapter cables are required for controllers with other connections.

For operation with a SATA controller, please order the corresponding number of the optional crossed SFF-8087 to 4x SATA cables (88885237).



IPC 4U-4724

Dimensions and Weight Cage Case Package Height 176mm 176mm 250mm Width 431mm 481mm 570mm Depth 655mm 685mm 855mm Weight (net): 15.58kg

ower Supply	L	
Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-,
P4/EPS 4+4Pin	-	4
P8 12V 8Pin	_ · _	417
PCI-Express 6+2Pip	460	UГ
PCI-Exp s	tho	_
IDE 4Pin		-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan Control	-	-
Fan: 120mm	-	-

Certification:

Weight (gross): 18.22kg