# ACCC AND CO. LAND CO.

# Inter-Tech Elektronik Handels GmbH

#### IPC 4U-4736



#### **IPC 4U-4736**

The **IPC 4U-4736** is the perfect rack for a small and cost-effective storage system. Due to the excellent material quality, in combination with excellent workmanship, Inter-Tech has created the basis for an extremely variable case.

The case offers the possibility of installing a maximum of 36x 2.5" or 3.5" hot-swap hard disks, as well as optionally two 2.5" internal hard disks. The IPC 4U-4736 is equipped with seven 80mm hot-swap hard disks installed as standard Fans equipped that reliably ensure optimal cooling.

Additional extras such as the reusable and perforated low-profile slot brackets, USB 2.0 connections and the case lid with snap-in closures complete this excellent overall package.



#### *IPC 4U-4736*

#### **Specifications**

Motherboard Mini ITX, μΑΤΧ, ΑΤΧ, eATX, SSI EEB maximal motherboard size BxT: 305mm x 345mm, 12" x 13.5" Drive bays 36x 2.5" or 3.5" Hot-Swap (max. 6G) 1x mounting bracket for 2x 2.5" Front connectors USB 2.0: 2 Cooling system Internal: 7x 80mm (7x serial, 4pin at backplane) Controls Power button Reset button UID button **LED** Power HDD activity 2x network activity Temperature alert Power supply 2U PSU 2U redundant PSU Material 1.0-1.2mm steel Maximum CPU cooler height 60mm Maximum graphics card length 340mm Packing units Shipping unit: 1 piece Pallet: 14 pieces Warranty 24 months 88887355 Article number 4260455647267 EAN-Code Scope of delivery Screws Mounting bracket for 2U (pre-mounted) and 2U 2-way redundant power supplies Mounting bracket internal for varius power supplies **Features** Standard 7x 80mm fans

7x perforated slot brackets

Lid with snap-in lock

2x 12-way S-ATA/SAS hot-swap backplane with 3x SFF-8087 socket<sup>1</sup>

The backplane is only suitable for operation on a SAS controller with a SFF-8087 connector.

Adapter cables are required for controllers with other connections.

For operation with a SATA controller, please order the corresponding number of the optional crossed SFF-8087 to 4x SATA cables (88885237).



### IPC 4U-4736

## <u>Dimensions and Weight</u>

Cage Case Package

Height 176mm 176mm 250mm

Width 431mm 481mm 570mm

Depth 655mm 685mm 855mm

Weight (net): 18.43kg Weight (gross): 21.07kg

| ower Supply        | L        |             |
|--------------------|----------|-------------|
| Connector          | Quantity | Max. Length |
| Mainboard 20+4Pin  | -        | -           |
| P4 12V 4Pin        | -        | -           |
| P4/EPS 4+4Pin      | -        | 4           |
| P8 12V 8Pin        | _ · _    | 417         |
| PCI-Express 6+2Pin | th0      | yı          |
| PCI-Express n      | rnv      | _           |
| IDE 4Pin           |          | -           |
| S-ATA              | -        | -           |
| Floppy             | -        | -           |
| RPM sensor cable   | -        | -           |
| Fan Control        | -        | -           |
| Fan: 120mm         | -        | -           |

Certification: