

Product information

IPC-C338

very short (380mm) 3U server case

Features

Drive bays	2x 5.25" ODD 5x 3.5" HDD 1x combined 5.25"/3.5"/2x2.25" drive bay Drive bays with anti-vibration function
Mainboard	mini-ITX, µATX, ATX
Power supply	PS/2 form factor with 8 14cm fan up to 140mm depth
Expansion	up to 4 expansionn cards up to 170-330mm depth
Ventilation	incl. 2x 8cm front mounted intake fans
Special features	Equipped with two front USB2.0 ports optional USB3.0 available
Handles	Durable strength plastic handles
Color	black, scratch-resistant
Dimensions	483 x 133 x 380mm (WxHxD)
Accessories	8x M3 round head nickel screw 24x
6 round head nickel screw 2x MB metal standoff 1x MB plastic standoff	
Material	SGCC material 1.2-2.0mm

Additional information

If a 140mm deep power supply gets installed, is in the 5.25"-shafts devices up to of a depth of 210mm possible

If a 180mm deep power supply gets installed is in the 5.25"-shafts devices up to of a depth of 170mm possible

If the front 3.5"-shafts is getting used , are expansion cards with of a length up to 170mm possible

If the front 3.5"-shafts is not getting used and the mounting plate gets removed, are expansion cards with of a length up to 330mm possible.

When a ATX mainboard is installed the combined 5.25"/3.5"2x2.5" drive bay (lower) can not be used.

Optional components

[Removable racks](#)

[Backplanes](#)

Shipping details

Carton dimensions	56 x 52 x 23cm (L x W x H)
Shipping weight	7,8 kg
Palet shipment	21-28 pcs

