) (NN) SIMPLY FAST	Products Whe	ere to Buy	Store Sup	port	News & Meo	lia About Sonnet	Partne	er Resources	
			Solo10G [™] PCle [®] Card 10GBASE-T 10 Gigabit Ethernet PCI Express 3.0 Adapter Card with NBASE-T Ethernet Support						
			Find a Dis	stributo	r/Reseller	Downloads, Manual	ls, FAQs	Register F	
Overview	Tech Specs	Vide	os						
Part No.			Com	puter	Compatibi	lity			
G10E-1X-E3	Solo10G PCIe Card 10GBASE-T/NBASE-T Ethernet PCI Expre Adapter Card	ess 3.0	Mac Pro® (Mid 2010 or newer), PC desktop, or server with full- height or low-profile PCIe slots						
Hardware					10.13.6+				
Warranty	2-year		macOS Catalina compatible						
Form Factor	Low-profile PCIe computer card		Windows® 10, 8, 7; Server 2016, 2012						
External Connector	One RJ45 port		Linu	IX®					
Bus Interface	PCI Express v3.0, x4		Thunderbolt Compatibility						
10GbE Controller	Aquantia AQC-107S		 Mac via a Thunderbolt 2 or Thunderbolt 3 to PCIe card expansi system 						
	• 10GBASE-T ● 100 meters using CAT6A cabling		Windows computer running Windows 10 Build 1809 or newer (64- bit edition), via a Thunderbolt 3 to PCIe card expansion system						
Network Support	 55 meters using CAT6 cabling 		Techn	ical No	tes				
	5GBASE-T, 2.5GBASE-T, 1000BASE- 100BASE-TX	5GBASE-T, 1000BASE-T,			1. 2.5G/5G speeds are supported when used with NBASE-T compatible (multi- Gigabit) switches. 2. Switch/router must support AVB to support this feature.				
	• 100 meters using CAT 5e (or better) ca	bling ⁽¹⁾							
Packets	Maximum packet size: 16352 bytes (jumb 9000 bytes under macOS	oo frames)	Mac	For Wit	ndows				
Data Rates Supported	10 Gb/s, 5 Gb/s, 2.5 Gb/s, 1 Gb/s, 100 Mb	o/s							
Advanced Features	 Flow control support MSI (Message Signaled Interrupts) RSS (Receive-Side Scaling) Interrupt coalescing Multicast filtering Energy-Efficient Ethernet (IEEE 802.3a AVB (IEEE 802.1Qav, Audio Video Bridge 64-bit address support for systems us than 4GB of physical memory PCIe networking cards cannot support LAN 	(²⁾ ing more							
Stateless Offloads	 TCP, UDP and IPv4 checksum offloadii TSO (TCP Segmentation Offload, AKA) 	-							

 • LRO (Large Receive Offload)

 • RSS (Receiver Side Scaling)

 RoHS Compliant

 Yes

 Package Contents
 • Solo10G PCle Card

 • Two mounting brackets (full-height and low-profile)

 • Documentation

Specifications subject to change without notice.

Home > Product > Solo10g Pcie Card

Copyright © 2020 Sonnet Technologies, Inc. All rights reserved. | Trademarks | 5 English | 🛄 Français | 5 Deutsch | 🔍 日本語 | 🔤 Español