

SuperChassis 732D3-1K26B



Key Features

1. 90° Rotatable HDD Cage
2. Whisper-Quiet (<21dB)
3. Kensington Lock Support
4. Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 3.0
5. 1x Optional Front 12cm (1850 RPM) PWM Fan
6. Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
7. 1200W **Platinum Level** Certified High-Efficiency Power Supply
8. 1x Rear 12cm (1850 RPM) PWM Fan
9. 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

Specifications

Product SKUs

CSE-732D3-1K26B	■ SuperChassis 732D3-1K26B
------------------------	----------------------------

Form Factor

- Mid-tower chassis support motherboard sizes E-ATX (12" x 13"), ATX (12" x 10") & Micro-ATX (9.6" x 9.6")

Processor Support

- Dual and Single Intel® and AMD processors

Dimensions

Height	■ 16.7" (424 mm)
Width	■ 7.6" (193 mm)
Depth	■ 20.68" (525 mm)
Gross Weight	■ 30 lbs (13.61 kg)
Net Weight	■ 27 lbs (12.25 kg)
Packaging (W x H x L)	■ 11.97" (304 mm) x 21.38" (543 mm) x 25.28" (642 mm)
Available Color	■ Black

Expansion Slots

- 7x Full-height, Full-length expansion slot(s)

Drive Bays

- Optional 4x 2.5" fixed drive bay
- 4x 3.5" fixed drive bay

Peripheral Drives

- 2x standard 5.25" drive bay
- 1x card reader module

Front Panel

Button	■ Power On/Off button
LED	■ HDD activity LED ■ 1 Network activity LEDs ■ System Information LED
Port	■ 2x USB 3.0 Port(s) ■ 1x Audio Jack(s)

Systems Cooling

Fans	■ Optional 1x 12cm (front) cooling fan ■ 1x 12cm rear exhaust fan(s)
-------------	---

Operating Environment (System)

Operating Temperature Range	■ 5°C - 35°C (41°F - 95°F)
Non-Operating Temperature Range	■ -40°C - 70°C (-40°F - 158°F)
Operating Relative Humidity Range	■ 8% - 90% (non-condensing)
Non Operating Relative Humidity Range	■ 5% - 95% (non-condensing)

Power Supply

1200W PS2 Multi-output power supply	
Power Efficiency	■ 94%
Total Output Power and Input	■ 1200W with Input 120 - 240Vac ■ 1000W with Input 100 - 120Vac
AC Input Frequency	■ 50-60Hz
Dimensions (L x W x H)	■ 185 x 150 x 86 mm
Output Type	■ 24pin ATX
-12V	■ Max: 0.3A / Min: 0A
+12V	■ Max: 99A / Min: 1A (120Vac - 240Vac) ■ Max: 83A / Min: 1A (100Vac - 120Vac)
+5V	■ Max: 20A / Min: 0.3A
+3.3V	■ Max: 20A / Min: 0.3A
+5Vsb	■ Max: 3A / Min: 0A

Certification	■  Platinum Certified
----------------------	---

Regulatory (Power Supply)

Power Supply Safety / EMC	■ BSMI ■ CCC ■ CE/EMC ■ FCC class B ■ UL/CB
----------------------------------	---

Components

Standard Parts List

	Part Number	Qty	Description
Bracket	MCP-250-73201-0N	1	SC732 PS2 Power Supply Bracket
Cable(s)	CBL-0071L	1	ROUND 16 TO 16 PIN RIBBON FP CABLE 30"L, LF
Cable(s)	CBL-0084L	1	16PIN FRONT CTRL SPLIT CONVECTOR 6",PB FREE
Cable(s)	CBL-0453L	1	USB3.0 Internal Cable-60cm(19pin Female to 19pin Female)
Cable(s)	CBL-0455L	1	HD/AC97 Audio Cable-60cm
Cable(s)	CBL-PWCD-0160-IS	1	PWCD,US,NEMA5-15P TO IEC60320 C13,6FT,16AWG,RoHS/REACH
Part(s)	MCP-290-73101-0B	1	Black Card Reader Dummy Cover for SC731D
Part(s)	MCP-120-00116-0N	7	Blank FH L-bracket with 4x4 vent holes
Fan(s)	FAN-0124L4	1	12 CMx12 CM fan
Front Bezel	MCP-210-73102-0B	1	SC731D Front Control Bezel Assembly w/o Card Reader
Drive Tray(s)	MCP-220-73101-0B	4	SC731 Tool-less Internal 3.5inch HDD Tray
Power Supply & Accessory	PWS-1K26P-PQ	1	1000W/1200W PS2 Multi output power supply with modular cable
Mounting Rail(s)	MCP-290-73102-0N	1	SC731 Card Reader Rail

Optional Parts List

	Part Number	Qty	Description
Adapter Cable	CBL-0454L	-	USB3.0 to 2.0 adapter cable - 30cm(19pin male to 9pin female)
Fan Kit	FAN-0124L4 • eStore	-	12cm (1850rpm) cooling Fan
HDD Kit	MCP-220-73201-0N • eStore	-	HDD Cage (4x Internal 2.5" fixed HDD bays)
HDD Tray Converter	MCP-220-73102-0N • eStore	-	2.5" to 3.5" SSD/HDD Adapter Tray for 731, 732, DS3, 842
LCD	MCP-220-00095-0B	-	5.25" USB LCD Kit

Servers (for CSE-732D3-1K26B)

[SYS-7039A-i](#)