


SuperServer 1029U-TRTP (Complete System Only)



Integrated Board



X11DPU

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

Complete System Only: To maintain quality and integrity, this product is sold only as a completely-assembled system (with minimum 2 CPUs and 4 DIMMs).

► [Drivers & Utilities](#) ► [BIOS](#) ► [IPMI](#) ► [Tested Memory](#) ► [Tested M.2 List](#) ► [NVMe Options](#) ► [Manuals](#) ► [OS Certification Matrix](#) ► [Compatible GPU List](#) ► [Quick-References Guide](#) ► [Drive Options](#) ► [Network Card \(AOC\) Matrix](#)

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Key Features

- ☐ **Virtualization**
- ☐ **Cloud Computing**
- ☐ **High End Enterprise Server**

1. Dual Socket P (LGA 3647) support
2nd Gen. Intel® Xeon® Scalable
processors (Cascade Lake/Skylake)[‡]
2. 24 DIMMs; up to 6TB 3DS ECC
DDR4-2933MHz[†] RDIMM/LRDIMM,
Supports Intel® Optane™ DCPMM^{††}
3. 2 PCI-E 3.0 x16 slots (FH, 10.5" L),
2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)
4. 2 10G SFP+ Ethernet ports
5. 10 Hot-swap 2.5" Drive Bays;
10 SATA3 (2 hybrid ports - 2 NVMe opt.);
Optional M.2 NVMe and SATA3 ports
6. 8 heavy duty fans w/ optimal
fan speed control
7. 750W Redundant Power Supplies
Platinum Level (94%+)

Specifications

Product SKUs

- SYS-1029U-TRTP** ■ SuperServer 1029U-TRTP (**Black**)

Motherboard

Super X11DPU

Processor/Cache

- CPU** ■ Dual Socket P (LGA 3647)
 - 2nd Gen. Intel® Xeon® Scalable Processors (Cascade Lake/Skylake)‡,
 - Dual UPI up to 10.4GT/s
- Support CPU TDP 70-205W

- Cores** ■ Up to 28 Cores

- Note** ‡ BIOS version 3.0a or above is required to support 2nd Gen. Intel® Xeon® Scalable processors

System Memory

- Memory Capacity** ■ 24 DIMM slots
 - Up to 6TB 3DS ECC DDR4-2933MHz†
 - RDIMM/LRDIMM
 - Supports Intel® Optane™ DCPMM††

- Memory Type** ■ 2933†/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM
 - 2666 ECC DDR4 NVDIMM

- Note** † 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro
 - †† Cascade Lake only. Contact your Supermicro sales rep for more info.

On-Board Devices

- Chipset** ■ Intel® C621 chipset
- SATA** ■ SATA3 (6Gbps); RAID 0, 1, 5, 10
- Network Connectivity** ■ 2 10G SFP+ ports via AOC-URN2-I2XS (Intel® 82599ES)
- IPMI** ■ Support for Intelligent Platform Management Interface v.2.0
 - IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
- Graphics** ■ ASPEED AST2500 BMC

Input / Output

- SATA** ■ 10 SATA3 (6Gbps) ports
- SAS** ■ 8 SAS3 ports support via optional Add-on Card
- LAN** ■ 2 10G SFP+ ports
 - 1 RJ45 Dedicated IPMI LAN port
- USB** ■ 5 USB 3.0 ports
 - (2 rear, 2 front, 1 Type A)
- Video** ■ 2 VGA ports (1 rear, 1 onboard)
- Serial Port** ■ 1 Serial header

System BIOS

Chassis

- Form Factor** ■ 1U Rackmount

- Model** ■ **CSE-119UTS-R751P-T**

Dimensions and Weight

- Height** ■ 1.7" (43mm)
- Width** ■ 17.2" (437mm)
- Depth** ■ 28.5" (724mm)
- Weight** ■ Net Weight: 26 lbs (11.8 kg)
 - Gross Weight: 41 lbs (18.6 kg)
- Available Color** ■ Black

Front Panel

- Buttons** ■ Power On/Off button
 - System Reset button
- LEDs** ■ Power LED
 - Hard drive activity LED
 - Network activity LEDs
 - System Overheat LED / Fan fail LED / UID LED

Expansion Slots

- PCI-Express** ■ 2 PCI-E 3.0 x16 (Full-height, 10.5" L)
 - 2 PCI-E 3.0 x8 (1 LP, 1 internal LP)

(Both CPUs need to be installed for full access to PCI-E slots and onboard controllers. See manual block diagram and [AOC Support](#) for details.)

Drive Bays / Storage

- Hot-swap** ■ 10 Hot-swap 2.5" drive bays; 10 SATA3 (2 hybrid ports - 2 NVMe opt.)
- M.2** ■ 1 M.2 PCI-E 3.0 x4 M-Key NVMe or 1 M.2 M-Key SATA3 (2240/2260/2280/22110) via optional riser card (see optional parts list)
 - 2 M.2 PCI-E 3.0 x4 M-Key NVMe (2260/2280/22110) via optional add-on card AOC-SLG3-2M2

System Cooling

- Fans** ■ 8 heavy duty fans with optimal fan speed control
- Air Shroud** ■ 1 Air Shroud

Power Supply

750W Redundant Power Supplies with PMBus

- Total Output Power** ■ 750W: 100 – 127Vac
 - 750W: 200 – 240Vac
- Dimension (W x H x L)** ■ 73.5 x 40 x 203 mm
- Input** ■ 100-127Vac / 9.5A Max / 50-60Hz
 - 200-240Vac / 4.5A Max / 50-60Hz
- +12V** ■ Max: 62.5A / Min: 0A

BIOS Type	■ AMI 32Mb SPI Flash ROM
------------------	--------------------------

Management	
Software	■ Intel® Node Manager ■ <u>IPMI 2.0</u> ■ KVM w ith dedicated LAN ■ NMI ■ <u>SSM, SPM, SUM</u> ■ <u>SuperDoctor® 5</u>

Power Configurations	■ ACPI Pow er Management
-----------------------------	--------------------------

PC Health Monitoring

CPU	■ Monitors for CPU Cores, Chipset Voltages, Memory. ■ 4+1 Phase-sw itching voltage regulator
------------	---

FAN	■ Fans w ith tachometer monitoring ■ Status monitor for speed control ■ Pulse Width Modulated (PWM) fan connectors
------------	--

Temperature	■ Monitoring for CPU and chassis environment ■ Thermal Control for fan connectors
--------------------	--

12V SB	■ Max: 2.1A / Min: 0A
---------------	-----------------------

Output Type	■ 25 Pairs Gold Finger Connector
--------------------	----------------------------------

Certification	 Platinum Level [<u>Test Report</u>]
----------------------	--

Operating Environment

RoHS	■ RoHS Compliant
-------------	------------------

Environmental Spec.	■ Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) ■ Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) ■ Operating Relative Humidity: 8% to 90% (non-condensing) ■ Non-operating Relative Humidity: 5% to 95% (non-condensing)
----------------------------	---

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11DPU	1	Super X11DPU Motherboard
	CSE-119UTS-R751P-T	1	CSE-119UTS-R751P-T Chassis
Add-on Card / Module	AOC-URN2-I2XS	1	1U Ultra Riser based on Intel 82599ES controller w ith 2 10Gb SFP+ ports, 2 NVMe ports, and 1 internal PCI-E x8 3.0 slot
Backplane	BPN-SAS3-116A-N2	1	10-port 1U SAS3 12Gbps Hybrid backplane, support up to 8x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-PWEX-0650	1	8 pin female to 2x RA(Right Angle) big 4 pin female pow er, 47/62CM, 18AWG,RoHS/REACH
Cable 2	CBL-PWEX-0653	1	8 pin female to 4 pin female pow er, 37cm, 18AWG,RoHS/REACH
Cable 3	CBL-SAST-0655	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,47CM,SB,30AWG
Cable 4	CBL-SAST-0657	1	MINI SAS HD(ST)-MINI SAS(RA-RS EXIT),6G,INT,55CM,SB,30AWG
Cable 5	CBL-SAST-1015-1	1	MINI SAS-2 SATA (RA),6G,INT,52CM,62CM SB,30AWG,RoHS
FAN 1	FAN-0101L4	4	40x56,4 Pin PWM,Primary for SC809,111, Sec.for SC816,819,808
Rear Window	MCP-240-81910-0N	1	Rear window for SC819U, 119U tool-less chassis (i2XS)
Air Shroud	MCP-310-81910-0N	1	Plastic air shroud for SC819U, 119U (X11 24DIMM, left side)
Air Shroud	MCP-310-81911-0N	1	Plastic air shroud for SC819U, 119U (X11 24DIMM, right side)
Riser Card	RSC-R1UW-2E16	1	1U LHS WIO Riser card w ith tw o PCI-E x16 slots
Riser Card	RSC-R1UW-E8R	1	1U RHS WIO Riser card w ith one PCI-E x8 slot
Heatsink / Retention	SNK-P0067PS	2	1U Passive CPU Heat Sink for X11 Purley Platform Equipped w ith a Narrow Retention Mechanism
* Power Supply	PWS-751P-1R	2	1U 750W Redundant Platinum Single Output Pow er Supply w /Pmbus W73.5xH40xL203mm,RoHS/REACH

Notes:

1. Parts with * are inside the chassis
2. Excessive parts might not be shipped, including but not limited to excessive drive trays, fans, riser brackets, air shrouds, IO shields, cables.....etc.

Optional Parts List

	Part Number	Qty	Description
Add-on card for internal M.2 NVMe	AOC-SLG3-2M2	1	Low Profile PCI-E x8 add-on card supports 2 PCI-E 3.0 x4 M-Key M.2 NVMe Modules
Internal Drive Tray for Two 2.5" Drives	MCP-120-82916-0N	1	Internal drive plate Supports Tw o 2.5" Drive, PCI slots
	CBL-PWEX-0650	1	Pow er cable for Tw o internal 2.5" drives
	CBL-0080L	2	
	CBL-0484L Or	2	SATA3 S-S Cable
	CBL-SAST-0654 Or	1	miniSAS(iPass) to 4 SATA Cable
	CBL-SAST-0948	1	miniSAS HD to 4 SATA Cable
Cable for 2 NVMe Hybrid Drive Bays	CBL-SAST-0929	2	OCuLink source to MiniSAS HD target V.91,INT,PCIe NVMe SSD, 57CM,34AWG
2.5" NVMe Drive Trays	MCP-220-00167-0B	1~2	Tool-less black hot-sw ap 2.5" NVMe drive tray (Orange tab, w / key lock, clip design)
	MCP-220-00127-0B		Black hot-sw ap 2.5" NVMe drive tray (Orange tab, w / key lock)
2 Internal M.2 slots (1 SATA, 1 NVMe)	RSC-UMR-8 & CBL-SAST-0538	1	1U Ultra RHS Riser Card w ith 1 PCIe/SATA Hybrid M.2 &1 PCIe X8

Storage Control Card and Cable(s)	AOC-S3008L-L8e & 2x CBL-SAST-0593	1	Std LP, 8 internal ports, 12Gb/s per port- Gen3, 122HDD, HBA; MINI SAS HD SATA, 12G,INT,60CM,60CM SB,30AWG
	AOC-S3008L-L8i & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 63HDD, RAID 0,1,1E; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 240HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
	AOC-S3108L-H8iR-16DD & 2x CBL-SAST-0593		Std LP, 8 internal ports, 12Gb/s per port- Gen3, 16HDD, RAID 0, 1, 5, 6, 10, 50, 60; MINI SAS HD,12G,INT,60CM,30AWG
Network Card(s)	AOC-SGP-i2/4	-	Standard LP, 2/4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i1S/i2S	-	Standard LP, 1/2x 10GbE SFP+, PCI-E x8, Intel 82599EN
	AOC-STGF-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel XL710-BM2
	AOC-STG-i4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Intel XL710
	AOC-STG-b4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STG-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X540
	AOC-STGS-i1/2T	-	Standard LP, 1/2x 10GbE RJ45, PCI-E x8, Intel X550
	AOC-STG-i4T	-	Standard LP, 4x 10GbE RJ45, PCI-E x8, Intel XL710
	AOC-STG-i2	-	Standard LP, 2x 10GbE CX4, PCI-E x8, Intel 82598EB
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, Mellanox ConnectX-4 LX EN
	AOC-S40G-i2Q	-	Standard LP 2-port 40GbE controller, Intel Fortville XL710
	More	-	AOC Compatibility Matrix
CacheVault(s)	BTR-CV3108-1U1	-	CacheVault for Broadcom 3108 w ith Supercap mounting in 1U 40x56 fan tray
	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108; Supercap mounting bracket for PCI-E location
1U Cable Management Arm	MCP-290-00152-0N	1	1U Supermicro Cable Management Arm 2nd Gen
TPM security module	AOM-TPM-9670H-S	1	TCG 2.0 compliant trusted platform module (TPM), Horizontal FF
	AOM-TPM-9671H-S	1	TCG 1.2 compliant trusted platform module (TPM), Horizontal FF
Intel VROC RAID Key	AOC-VROCIINTMOD	1	Intel VROC, RAID 0, 1, 5, 10 (Intel SSD Only)
	AOC-VROCSTNMOD	1	Intel VROC Standard, RAID 0, 1, 10
	AOC-VROCPREMOD	1	Intel VROC Premium, RAID 0, 1, 5, 10
Global Services & Support	OS4HR3/2/1	-	3/2/1-year onsite 24x7x4 service
	OSNBD3/2/1	-	3/2/1-year onsite NBD service
Software	SFT-OOB-LIC • eStore	1	OOB Management Package (per node license)
Software	SFT-DCMS-Single	1	DataCenter Management Package (per node license)