

SuperServer 5019S-W4TR



Integrated Board



Super X11SSW-4TF

Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |

[▶ Drivers & Utilities](#) | [▶ BIOS](#) | [▶ IPMI](#) | [▶ Tested Memory](#) | [▶ Tested M.2 List](#) | [▶ Manuals](#) | [▶ OS Certification Matrix](#) | [▶ Quick-References Guide](#) | [▶ Drive Options](#) | [▶ Network Card \(AOC\) Matrix](#)

Key Features

□ Mainstream, WIO

1. Single Socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v6/v5, Intel® 7th/6th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
2. Intel® C236 chipset
3. 4 Hot-swap 3.5" SATA3 drive bays
4. Up to 64GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slots
5. 1 PCI-E 3.0 x16 or 2 PCI-E 3.0 x8
6. 4x 10GBase-T ports with Intel® X540, 1 dedicated IPMI port
7. 1 VGA, 1 COM, 2 USB 3.0, 2 USB 2.0
8. 500W Redundant Platinum Level power supplies

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs

- SYS-5019S-W4TR** ■ SuperServer 5019S-W4TR (Black)

Motherboard

Super X11SSW-4TF

Processor/Cache

- CPU** ■ Single Socket H4 (LGA 1151) supports:
■ Intel® Xeon® processor E3-1200 v6/v5,
■ CPU TDP up to 80W
- Note** BIOS version 2.0 or above is required to support Intel® Xeon® Processor E3-1200 v6 series or 7th Generation Intel® Core™ Processors

System Memory

- Memory Capacity** ■ 4x 288-pin DDR4 DIMM slots
■ Up to 64GB DDR4 ECC UDIMM
- Memory Type** ■ 2400/2133/1866/1600MHz ECC DDR4 SDRAM 72-bit, 288-pin (UDIMM) gold-plated DIMMs
- DIMM Sizes** ■ 16GB, 8GB, 4GB
- Memory Voltage** ■ 1.2 V
- Error Detection** ■ Corrects single-bit errors
■ Detects double-bit errors (using ECC memory)

On-Board Devices

- Chipset** ■ Intel® C236 chipset
- SATA** ■ SATA3 (6Gbps) via C236 controller
■ RAID 0, 1, 5, 10 support
- IPMI** ■ Support for Intelligent Platform Management Interface v.2.0
■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
■ ASPEED AST2400 BMC
- Network Controllers** ■ Quad LAN with Intel® X540 10GBase-T Ethernet Controller
■ Supports 10GBASE-T, 100BASE-TX, and 1000BASE-T, RJ45 output
- Video** ■ ASPEED AST2400 BMC

Input / Output

- SATA** ■ 6 SATA3 (6Gbps) ports
- LAN** ■ 4 RJ45 10GBase-T LAN ports
■ 1 RJ45 dedicated IPMI LAN port
- USB** ■ 5 USB 3.0 ports (2 rear + 2 headers + 1 Type A)
■ 6 USB 2.0 ports (2 rear + 4 headers)
- Video** ■ 1 VGA port
- Serial Port / Header** ■ 2 COM ports (1 rear, 1 header)
- SuperDOM** ■ 2 SuperDOM (Disk on Module) ports with built-in power

Chassis

- Form Factor** ■ 1U Rackmount

- Model** ■ CSE-815TQC-R504WB3

Dimensions and Weight

- Height** ■ 1.7" (43mm)
- Width** ■ 17.2" (437mm)
- Depth** ■ 25.6" (650mm)
- Package** ■ 23.5" (W) x 8.5" (H) x 33.7" (L)
- Weight** ■ Net Weight: 24 lbs (10.9 kg)
■ Gross Weight: 35 lbs (15.9 kg)
- Available Colors** ■ Black

Front Panel

- Buttons** ■ Power On/Off button
■ System Reset button
- LEDs** ■ Power LED
■ Hard drive activity LED
■ Network activity LEDs
■ System Information LED
■ Information LED (temp., status)

Expansion Slots

- PCI-Express** ■ 1 PCI-E 3.0 x16 or 2 PCI-E 3.0 x8
- M.2** ■ 1x M.2 Interface: PCI-E 3.0 x4
■ Form Factor: 2260, 2280, 22110
■ Key: M-Key
■ Double Height Connector

Drive Bays

- Hot-swap** ■ 4 Hot-swap 3.5" SATA3 drive bays

Peripheral Drives

- DVD-ROM** ■ 1 Slim DVD-ROM drive bay

Backplane

- SAS/SATA HDD Backplane
(SAS support requires optional SAS controller)

System Cooling

- Fans** ■ 4x 40x56mm counter-rotation PWM fan
■ Optional 2x 40x56mm counter-rotation fans

Power Supply with Power Distributor

- 500W high-efficiency (94+%) power supply w/ PMBus

- With Power Distributor** ■ +5V: 25 Amp
■ +3.3V: 12 Amp
■ -12V: 0.6 Amp

Certification



Platinum Certified

[Test Report]

PC Health Monitoring

Voltage	<ul style="list-style-type: none">Monitors for CPU Cores, +3.3V, +5V, +12V, +5V Standby, VBAT, HT, Memory, Chipset Voltages.
FAN	<ul style="list-style-type: none">Total of 6 fan headers supporting up to 6 fans3 fans with tachometer status monitoringStatus monitor for speed controlStatus monitor for on/off controlLow noise fan speed controlPulse Width Modulated (PWM) fan connectors
Temperature	<ul style="list-style-type: none">Monitoring for CPU and chassis environmentCPU thermal trip supportI²C temperature sensing logicThermal Monitor 2 (TM2) supportPECI
LED	<ul style="list-style-type: none">System Information LEDSuspend static indicator LEDUID/Remote UID
Other Features	<ul style="list-style-type: none">Chassis intrusion detectionChassis intrusion headerRoHS, Halogen Free

System BIOS

BIOS Type	<ul style="list-style-type: none">8MB SPI Flash EEPROM with AMI BIOS
------------------	--

Operating Environment / Compliance

RoHS	<ul style="list-style-type: none">RoHS Compliant
-------------	--

Environmental Spec.	<ul style="list-style-type: none">Operating Temperature:<ul style="list-style-type: none">10°C to 35°C (50°F to 95°F)Non-operating Temperature:<ul style="list-style-type: none">-40°C to 70°C (-40°F to 158°F)Operating Relative Humidity:<ul style="list-style-type: none">8% to 90% (non-condensing)Non-operating Relative Humidity:<ul style="list-style-type: none">5% to 95% (non-condensing)
----------------------------	--

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11SSW-4TF	1	Super X11SSW-4TF Motherboard
	CSE-815TQC-R504WB3	1	1U Chassis
Backplane	BPN-SAS3-815TQ-N4	1	4-port 1U SAS3 12Gbps Hybrid backplane, support up to 4x 3.5-inch SAS3/SATA3/NVMe Storage Devices
Cable 1	CBL-0180L-01	1	SATA,INT,ROUND,SET OF 4,ST-RA 70/59/48/38CM,26AWG
Cable 2	CBL-CDAT-0660	1	CBL,SGPIO,2X4F TO 2X4F,P2.54,ROUND CABLE,27CM,28AWG
FAN 1	FAN-0156L4	4	40x40x56 mm 13K-11K RPM Counter-rotating Fan,RoHS/REACH
Air Shroud	MCP-310-19002-0N	1	SC815/113/116 Intel DP X9, X8 PC air shroud, 12x13MB
Manual	MNL-1990-QRG	1	5019S-W4TR Quick Reference Guide
Riser Card	RSC-W-68	1	1U LHS WIO w / 2 PCI-E x8 slots or PCI-E x16 slot
Heatsink / Retention	SNK-P0046P	1	1U PASSIVE CPU HS FOR INTEL LGA 1156
Power Supply	PWS-504P-1R	2	500W 1U Redundant PWS W/ 54.5MM Wide

Optional Parts List

	Part Number	Qty	Description
2.5" to 3.5" Converter Tray	MCP-220-00043-0N	-	Black Hot-sw ap Gen-4 2.5" to 3.5" HDD tray
DVD-ROM / DVD-RW	DVM-TEAC-DVD-SBT4	1	TEAC slim DVD-ROM SATA drive
	DVM-TEAC-DVD-SBT4	1	PHILIPS slim DVD-RW SATA drive
DVD-ROM Accessory	MCP-220-81502-0N	1	Slim SATA DVD mounting kit
Internal 2.5" HDD Tray (FDD slot)	MCP-220-83601-0B	1	Black FDD dummy tray support 1x 2.5" slim HDD
Internal 2.5" HDD Tray (DVD slot)	MCP-290-00036-0B	1	Black DVD dummy tray support 1x 2.5" slim HDD
Cable for internal HDD	CBL-0484L	2	55cm 30AWG SATA straight to straight cable
	CBL-0289L	1	Y split, big 4 pin to two RA SATA power extension 30cm
Hot-swap 2.5" kit (FDD slot)	MCP-220-81504-0N	1	Single slim 2.5" SAS3 (12Gb/s) hot swap in slim FDD form factor
Hot-swap 2.5" kit (DVD slot)	MCP-220-81506-0N	1	Single slim 2.5" SAS3 (12Gb/s) hot swap in slim DVD form factor
Cooling Fan	FAN-0156L4	-	40x40x56mm 13K-11K RPM Counter-rotating Fan
Storage Controller card & cable	AOC-S3108L-H8iR & 1x CBL-SAST-0699	-	Standard LP, 8 Internal ports (12Gb/s) PCI-E 3.0 x8, RAID controller, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3108L-H8iR-16DD & 1x CBL-SAST-0699	-	Standard LP, 8 Internal ports (12Gb/s) PCI-E 3.0 x8, 16HDD RAID controller, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3008L-L8i & 1x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) PCI-E 3.0 x8, 63HDD, RAID 0, 1, 10
	AOC-S3008L-L8e & 1x CBL-SAST-0699	-	Standard LP, 8 internal ports (12Gb/s) PCI-E 3.0 x8, 122HDD HBA
CacheVault	BTR-CV3108-1U1	-	CacheVault for Broadcom 3108 with SuperCap mounting in 1Y 40x56 fan tray
	BTR-TFM8G-LSICV/M02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108 with SuperCap mounting bracket for PCI-E location
Network Card(s)	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350-AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGF-i2S	-	Standard LP, 2x 10GbE SFP+, PCI-E x8, Intel X710-BM2
	AOC-STG-B4S	-	Standard LP, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGS-i2T	-	Standard LP, 2x 10GbE RJ45, PCI-E x8, Intel X550-AT2
	AOC-S25G-b2S	-	Standard LP, 2x 25GbE SFP28, PCI-E x8, Broadcom BCM57414
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, PCI-E x8, Mellanox CX-4 LX

Front Bezels	<u>CSE-PTFB-813LB</u>	-	Black front bezels
	<u>CSE-PTFB-813-02B</u>	-	Black Front Bezel w / Round Venting Holes
TPM security module	<u>AOM-TPM-9665V</u>	1	TPM 2.0, vertical form factor
	<u>AOM-TPM-9655V</u>	1	TPM 1.2, vertical form factor
Global Services & Support	<u>OS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>OSNBD3/2/1</u>	-	3/2/1-year onsite NBD service
Software	<u>SFT-OOB-LIC</u> • <i>eStore</i>	1	OOB Management Package (per node license)
Software	<u>SFT-DCMS-Single</u>	1	DataCenter Management Package (per node license)