

SuperServer 5029P-WTR



Integrated Board



Super X11SPW-TF

**Views: | [Angled View](#) | [Top View](#) |
| [Front View](#) | [Rear View](#) |**

[▶ Drivers & Utilities](#) ▶ [BIOS](#) ▶ [IPMI](#) ▶ [Tested Memory](#) ▶ [Tested M.2 List](#) ▶ [Manuals](#) ▶ [OS Certification Matrix](#) ▶ [Quick-References Guide](#) ▶ [Drive Options](#) ▶ [Network Card \(AOC\) Matrix](#)

Key Features

- ❑ **DB Processing & Storage**
- ❑ **Connectivity/Storage Computer Nodes**
- ❑ **Data Warehouse**

1. Single Socket P (LGA 3647) supports 2nd Gen. Intel® Xeon® Scalable processor (Cascade Lake/Skylake)[‡]
2. 6 DIMMs; up to 1.5TB 3DS ECC DDR4-2933MHz[†] RDIMM/LRDIMM
3. 4 PCI-E 3.0 x8 (FHFL) slots, 1 PCI-E 3.0 x8 (LP) slot
4. 8 Hot-swap 3.5" SATA3 drive bays
5. 2x 10GBase-T ports with Intel X722 + X557
6. 1 VGA, 2 COM, 4 USB 3.0, 2 USB 2.0
7. 2 SuperDOM (Disk on Module) ports
8. 500W Redundant Platinum Level power supplies

Note: Image above may show a varied configuration of optional parts. Please refer to parts list for standard parts included.

Specifications

Product SKUs

- SYS-5029P-WTR** ■ SuperServer 5029P-WTR (**Black**)

Motherboard

Super X11SPW-TF

Processor/Cache

- | | |
|--------------|--|
| CPU | ■ Single Socket P (LGA 3647)
■ 2nd Gen. Intel® Xeon® Scalable Processors (Cascade Lake/Skylake)†
■ Support CPU TDP 70-205W |
| Cores | ■ Up to 28 Cores |
| Note | † BIOS version 3.0b or above is required to support 2nd Gen. Intel® Xeon® Scalable processors |

System Memory

- | | |
|------------------------|--|
| Memory Capacity | ■ 6 DIMM slots
■ Up to 1.5TB 3DS ECC DDR4-2933MHz† RDIMM/LRDIMM |
| Memory Type | ■ 2933†/2666/2400/2133MHz ECC DDR4 RDIMM/LRDIMM |
| Note | † 2933MHz in two DIMMs per channel can be achieved by using memory purchased from Supermicro
†† Cascade Lake only. Contact your Supermicro sales rep for more info. |

On-Board Devices

- | | |
|----------------------------|--|
| Chipset | ■ Intel® C622 chipset |
| SATA | ■ SATA3 (6Gbps); RAID 0, 1, 5, 10 |
| Network Controllers | ■ Dual 10GBase-T LAN with Intel® X722 + X557 |
| IPMI | ■ Support for Intelligent Platform Management Interface v.2.0
■ IPMI 2.0 with virtual media over LAN and KVM-over-LAN support |
| Video | ■ ASPEED AST2500 BMC |

Input / Output

- | | |
|-----------------------------|---|
| SATA | ■ 10 SATA3 (6Gbps) ports |
| LAN | ■ 2 RJ45 10GBase-T LAN ports
■ 1 RJ45 dedicated IPMI LAN port |
| USB | ■ 5 USB 3.0 ports (2 rear + 2 headers + 1 Type A)
■ 7 USB 2.0 ports (2 rear + 5 headers) |
| Video | ■ 1 VGA port |
| Serial Port / Header | ■ 2 COM ports (1 rear, 1 front) |
| SuperDOM | ■ 2 <u>SuperDOM</u> (Disk on Module) ports with built-in power |

System BIOS

- BIOS Type** ■ AMI 32Mb SPI Flash ROM

Chassis

- | | |
|--------------------|----------------------------|
| Form Factor | ■ 2U Rackmount |
| Model | ■ CSE-825TQC-R500WB |

Dimensions and Weight

- | | |
|-------------------------|--|
| Height | ■ 3.5" (89mm) |
| Width | ■ 17.2" (437mm) |
| Depth | ■ 25.5" (647mm) |
| Package | ■ 26.5" (W) x 11" (H) x 34" (L) |
| Weight | ■ Gross Weight: 59 lbs (26.76 kg)
■ Net Weight: 34 lbs (15.42 kg) |
| Available Colors | ■ Black |

Front Panel

- | | |
|----------------|--|
| Buttons | ■ Power On/Off button
■ System Reset button |
| LEDs | ■ Power LED
■ Hard drive activity LED
■ Network activity LEDs
■ System Information LED
■ Information LED (temp., status) |

Expansion Slots

- | | |
|--------------------|--|
| PCI-Express | ■ 4 PCI-E 3.0 x8 (FHFL) slots
■ 1 PCI-E 3.0 x8 (LP) slot |
| M.2 | ■ 1x M.2 Interface: PCI-E 3.0 x4 and SATA
■ Form Factor: 2280, 22110
■ Key: M-Key
■ Double Height Connector |

Drive Bays

- Hot-swap** ■ 8 Hot-swap 3.5" SATA3 drive bays

Peripheral Drives

- DVD-ROM** ■ 1 Slim DVD-ROM drive bay

System Cooling

- Fans** ■ 3 Hot-swap 8cm PWM cooling fans

Power Supply with Power Distributor

500W high-efficiency redundant power supplies with PMBus

- | | |
|-------------------------------|---|
| AC Input | ■ 100-240 V, 50-60 Hz, 6.1-2.6 Amp |
| DC Output | ■ 4 Amp @ +5V standby
■ 41.7 Amp @ +12V |
| With Power Distributor | ■ +5V: 30 Amp
■ +3.3V: 24 Amp
■ -12V: 0.6 Amp |

Certification



Platinum Certified
[**Test Report**]

Operating Environment

Management

Software	■ Intel® Node Manager ■ <u>IPMI 2.0</u> ■ KVM with dedicated LAN ■ NMI ■ <u>SPM, SUM</u> ■ <u>SuperDoctor® 5</u> ■ Watch Dog
Power Configurations	■ ACPI / APM Power Management

PC Health Monitoring

CPU	■ Monitors for CPU Cores, Chipset Voltages, Memory. ■ 4+1 Phase-switching voltage regulator
FAN	■ Fans with tachometer monitoring ■ Status monitor for speed control ■ Pulse Width Modulated (PWM) fan connectors
Temperature	■ Monitoring for CPU and chassis environment ■ Thermal Control for fan connectors

RoHS	■ RoHS Compliant
Environmental Spec.	■ Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) ■ Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) ■ Operating Relative Humidity: 8% to 90% (non-condensing) ■ Non-operating Relative Humidity: 5% to 95% (non-condensing)

Parts List

Parts List - (Items Included)

	Part Number	Qty	Description
Motherboard / Chassis	MBD-X11SPW-TF	1	Super X11SPW-TF Motherboard
	CSE-825TQC-R500WB	1	1U Chassis
Backplane	BPN-SAS3-825TQ	1	8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
Cable 1	CBL-0228L	3	SATA,INT,ROUND,ST-RA,55CM,26AWG
Cable 2	CBL-0230L	1	SATA,INT,ROUND,ST-RA,65CM,26AWG
Cable 3	CBL-0388L-01	1	MINI SAS-4 SATA (RA),INT,75/75/90/90CM,75CM SB,30AWG
Cable 4	CBL-CDAT-0660	1	CBL,SGPIO,2X4F TO 2X4F,P2.54,ROUND CABLE,27CM,28AWG
Drive Tray(s)	MCP-220-00114-0N	1	Black 2x USB3.0/COM port tray in slim DVD bay,RoHS/REACH
Manual	MNL-1922-QRG	1	QRG,HF,RoHS/REACH
Riser Card	RSC-R2UW-4E8	1	2U LHS WIO Riser card with four PCI-E x8 slots
Riser Card	RSC-R2UW-E8R-UP	1	2U RHS WIO Riser Card with a PCI-E x8 for UP MBs
Heatsink / Retention	SNK-P0068PS	1	2U Passive CPU Heat Sink for X11 Purley Platform Equipped with a Narrow Retention Mechanism
Power Supply	PWS-501P-1R	2	500W 1U Platinum redundant power supply
FAN 1	FAN-0126L4	3	80x80x38 mm 7K RPM Chassis Middle Fan w / Housing

Optional Parts List

	Part Number	Qty	Description
2.5" to 3.5" Converter Tray	MCP-220-00043-0N	-	Black Hot-sw ap Gen-4 2.5" to 3.5" HDD tray
DVD-ROM / DVD-RW	DVM-TEAC-DVD-SBT5	1	BLACK TEAC SLIM DVD SATA DRIVE
	DVM-PLDS-DVDRW-SBT5	1	PHILIPS SLIM BLACK DVD-RW SATA DRIVE
DVD-ROM Accessory	MCP-220-81502-0N	1	Slim SATA DVD mounting kit
Cable for internal HDD	CBL-0484L	2	55cm 30AWG SATA straight to straight cable
	CBI-0289L	1	Y split, big 4 pin to two RA SATA power extension 30cm
Storage Controller card & cable	AOC-S3108L-H8iR & 2x CBL-SAST-0699	-	Standard LP, 8 Internal ports (12Gb/s) PCI-E 3.0 x8, RAID controller, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3108L-H8iR-16DD & 2x CBL-SAST-0699		Standard LP, 8 Internal ports (12Gb/s) PCI-E 3.0 x8, 16HDD RAID controller, RAID 0, 1, 5, 6, 10, 50, 60
	AOC-S3008L-L8i & 2x CBL-SAST-0699		Standard LP, 8 internal ports (12Gb/s) PCI-E 3.0 x8, 63HDD, RAID 0, 1, 10
	AOC-S3008L-L8e & 2x CBL-SAST-0699		Standard LP, 8 internal ports (12Gb/s) PCI-E 3.0 x8, 122HDD HBA
CacheVault	BTR-TFM8G-LSICVM02 & BKT-BBU-BRACKET-05	-	CacheVault for Broadcom 3108 with SuperCap mounting bracket for PCI-E location
	BTR-TFM8G-LSICVM02 & MCP-240-00127-0N	-	CacheVault for Broadcom 3108 with SuperCap mounting bracket for internal fixed bay
Network Card(s)	AOC-SGP-i2	-	Standard LP, 2x GbE RJ45, PCI-E x4, Intel i350-AM2
	AOC-SGP-i4	-	Standard LP, 4x GbE RJ45, PCI-E x4, Intel i350
	AOC-STGN-i2S	-	Standard Lp, 2x 10GbE SFP+, PCI-E x8, Intel 82599ES
	AOC-STGF-i2S	-	Standard Lp, 2x 10GbE SFP+, PCI-E x8, Intel X710-BM2
	AOC-STG-B4S	-	Standard Lp, 4x 10GbE SFP+, PCI-E x8, Broadcom BCM57840S
	AOC-STGS-i2T	-	Standard Lp, 2x 10GbE RJ45, PCI-E x8, Intel X550-AT2
	AOC-S25G-b2S	-	Standard LP, 2x 25GbE SFP28, PCI-E x8, Broadcom BCM57414
	AOC-S25G-m2S	-	Standard LP, 2x 25GbE SFP28, PCI-E x8, Mellanox CX-4 LX
Front Bezels	MCP-210-82503-0B	1	Black front bezels
TPM security module	AOM-TPM-9670V	1	TPM 2.0, vertical form factor
	AOM-TPM-9671V	1	TPM 1.2, vertical form factor

Global Services & Support	<u>OS4HR3/2/1</u>	-	3/2/1-year onsite 24x7x4 service
	<u>OSNBD3/2/1</u>	-	3/2/1-year onsite NBD service
Software	<u>SFT-OOB-LIC</u> • <i>eStore</i>	1	OOB Management Package (per node license)
Software	<u>SFT-DCMS-Single</u>	1	DataCenter Management Package (per node license)