



Key Features

Intel® Xeon® E-2300 Processor, 10th Generation Intel® Pentium® Processor, Single Socket LGA-1200 (Socket H5) supported, CPU supports Up to 95W TDP

Intel® C252

Up to 64GB Unbuffered ECC UDIMM, DDR4-3200MHz, in 2 DIMM slots

1 PCI-E 4.0 x16

M.2 Interface: 1 PCI-E 3.0 x4

M.2 Form Factor: 2280

M.2 Key: M-Key

Dual LAN with Intel® i210 Gigabit Ethernet Controller

Intel® C252 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10

1 VGA D-Sub Connector port

2 SuperDOM with built-in power

4x USB 3.2 Gen1 (2 rear, 2 via header), 4x USB 2.0 (2 rear, 2 via headers)

Product SKUs

- MBD-X12STL-IF ■ X12STL-IF

Physical Stats

- **Form Factor** ■ Mini-ITX
- **Dimension** ■ 6.7" x 6.7" (17.02cm x 17.02cm)

Processor

- **CPU** ■ 10th Generation Intel® Pentium® Processor, Intel® Xeon® E-2300 Processor
- Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 95W TDP
- **Core** ■ Up to 8 cores

System Memory

- **Memory Capacity** ■ 2 DIMM slots
- Up to 64GB ECC UDIMM, DDR4-3200MHz
- **Memory Type** ■ 3200/2933/2666MHz SDRAM
- **DIMM Sizes** ■ 4GB, 8GB, 16GB, 32GB
- **Memory Voltage** ■ 1.2V
- **Error Detection** ■ Corrects single-bit errors

On-Board Devices

- **Chipset** ■ Intel® C252
- **SATA** ■ Intel® C252 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- **IPMI** ■ ASPEED AST2600 BMC
- **Graphics** ■ ASPEED AST2600 BMC
- **Network Controllers** ■ Dual LAN with Intel® i210 Gigabit Ethernet Controller

Input / Output

- **SATA** ■ 6 SATA3 (6Gbps) port(s)
- **LAN** ■ 2 RJ45 Gigabit Ethernet LAN ports
- **USB** ■ 4 USB 2.0 port(s) (2 rear; 2 via header)
- 4 USB 3.2 Gen1 port(s) (2 via header; 2 rear)
- **Video Output** ■ 1 VGA D-Sub Connector port(s)
- **Serial Port** ■ 1 COM Port(s) (1 rear)
- **DOM** ■ 2 SATA DOM (Disk on Module) power connector support
- **TPM** ■ 1 TPM Header

Expansion Slots

- **PCI-E** ■ 1 PCI-E 4.0 x16
- **M.2** ■ M.2 Interface: 1 PCI-E 3.0 x4
- Form Factor: 2280
- Key: M-Key

System BIOS

- **BIOS Type** ■ 256MB UEFI
- **BIOS Features** ■ ACPI 6.0
- SMBIOS 3.3
- Plug and Play (PnP)
- RTC (Real Time Clock) Wakeup
- UEFI 2.7
- USB Keyboard support
- PCI 3.0

Management

- **Software** ■ SuperDoctor® 5, SUM, SPM, SSM, IPMI2.0, Watchdog
- **System Management Software** ■ IPMI (Intelligent Platform Management Interface) v1.5 / 2.0 with KVM support
- **Power Configurations** ■ Power-on mode for AC power recovery, ACPI Power Management

PC Health Monitoring

- **Voltage** ■ VBAT, System level control, Supports system management utility, Monitors CPU voltages, Chipset Voltage, Chassis intrusion header, 4 -fan status, 3.3V standby, +5V standby, +5V, +3.3V, +12V, +1.8V, Memory Voltages
- **LED** ■ UID/Remote UID
- CPU / System Overheat LED
- **Temperature** ■ Monitoring for CPU and chassis environment
- CPU thermal trip support
- Thermal Monitor 2 (TM2) support
- PECI
- **FAN** ■ 4x4-pin fan headers (up to 4 fans)
- Thermal control tachometer fan connectors
- Fan speed control
- 4 fans with tachometer monitoring
- Overheat LED indication
- **Other Features** ■ WOL, UID, M.2 NGFF connector, Dual Cooling Zones, CPU thermal trip support for processor protection, Control of power-on for recovery from AC power loss, Chassis intrusion detection, ACPI power management

Operating Environment

- **Operating Temperature Range** ■ 0°C - 50°C (32°F - 122°F)
- **Non-Operating Temperature Range** ■ -20°C - 60°C (-4°F - 140°F)
- **Operating Relative Humidity Range** ■ 10% - 85% (non-condensing)
- **Non Operating Relative Humidity Range** ■ 10% - 95% (non-condensing)