

OUTPUT WATTAGE

400W

BEST SOLUTION FOR

Server ,Workstation ,PCs

DIMENSION

140x150x86(mm)

5.51x5.91x3.39(inch)

INPUT SPEC

VOLTAGE: 90~240 VAC FULL RANGE

FREQUENCY: 47~63HZ

INPUT CURRENT: 6A/3A FOR 115/230VAC

INRUSH CURRENT: 20/40 MAX. FOR 115/230VAC

DC OUTPUT SPEC

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
+5V	0.5	20	±5%	±50mV	50mV
+12V	1	30	±5%	±50mV	120mV
-12V	0	0.8	±5%	±50mV	120mV
+3.3V	0.5	20	±5%	±50mV	50mV
+5VSB	0.1	3.5	±5%	±50mV	50mV

FEATURES

*TEMPERATURE RANGE: OPERATING 0°C ~ 50°C; STORAGE -20°C ~ 80°C

*HOLD UP TIME: 16ms MINIMUM AT FULL LOAD & NORMAL INPUT VOLTAGE

*EFFICIENCY: 80-85% TYPICAL AT 115V FULL LOAD

*POWER GOOD SIGNAL: ON DELAY 100ms TO 500ms, OFF DELAY 1ms

*OVER POWER PROTECTOIN

*OVER VOLTAGE PROTECTOIN

*SHORT CIRCUIT PROTECTION

*OVER CURRENT PROTECTION

*SAFETY: TO MEET UL, CUL, TUV, CCC

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.