

OUTPUT WATTAGE

400W

BEST SOLUTION FOR

Server ,Workstation ,Storage System ,IPC ,PCs

DIMENSION

140x150x86(mm)

5.51x5.91x3.39(inch)

INPUT SPEC

VOLTAGE: 90 ~ 264 VAC FULL RANGE

DC OUTPUT SPEC

Output Voltage	Output Current Min.	Output Current Max.	Regulation Load	Regulation Line	Output Ripple & Noise Max.[P-P]
5V	3	35	± 5%	± 1%	50mV
12V	2	30	+7% ~ -5%	± 1%	120mV
-5V	0	0.5	±5%	± 1%	150mV
-12V	0	0.8	±5%	± 1%	150mV
+3.3V	1	28	± 5%	± 1%	50mV
+5VSB	0.1	2	± 5%	± 1%	50mV

REMARKS: THE OUTPUT CURRENT OF 5V & 3.3V NOT EXCEED 45A

FEATURES

*12V MAX. CURRENT: 30A

*NOISE & THERMAL CONTROL(SILENCE & RELIABLE)

*TEMPERATURE RANGE: OPERATING -10°C ~ 45°C

*EFFICIENCY: 70% AT 115V, FULL LOAD

* HUMIDITY:OPERATING:20%-95%, NON-OPERATING:10%-95%

* REMARKS:85% IS NORMAL CONDITION AND 95% IS WITH SPECIAL COATING PROCESS

*COOLING: ONE 80mm DC FAN

*ACTIVE POWER FACTOR CORRECTION MEET IEC-1000-3-2 CLASS D

*EMI NOISE FILTER: FCC CLASS B, CISPR22 CLASS B

*SAFETY: UL, CSA 22.2 NO/ 60950, TUV, CCC

*Serial ATA optional

*THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS.